





DR3

Versatile Stand-alone Tag & Label Printing Solution for in-store Retail Applications



Fast speed printing



Durability




Enduring



Stand-alone printing solution – No PC required
Manage label printing using the keypad



Speed and quality printing



Specially-designed accessories (cutter & stacker) for convenient on-demand printing



Accommodates large label rolls

DR3

General specifications



PRINTING SPECIFICATIONS		
Print Method	Direct Thermal/Thermal Transfer	
Print Resolution	8 dots/mm (203dpi)	
Max Print Speed	127mm/sec (5ips)	
Max Print Area (Width)	80mm, 3.15"	
Max Print Area (Pitch)	181mm, 7.13"	
MEDIA SPECIFICATIONS		
Sensor Type	Reflective Sensor (for use with pre-printed marks) · See-Through Sensor (for die-cut labels with gaps and tags with center or side holes) · Jump hole Sensor (for tags with jump hole)	
Sensor Type	Reflective Sensor (for use with pre-printed marks) See-Through Sensor (for die-cut labels with gaps and tags with center or side holes) Jump hole Sensor (for tags with jump hole)	
Media thickness	0.070 ~ 0.280 mm	
Media Roll Size	Outer Diameter Max 250mm, 9.84" (Paper core size : 38.1mm, 101.60mm, 1.5", 4")	
Ribbon	Width Max:	84mm, 3.31"
	Length Max:	300m, 984.25ft (varies on ribbon type)
	Winding Direction	Face-in
	Winding Method	Paper core
MEMORY/PROCESSING		
Main Memory	Flash-ROM 8MB	
CPU	33 bit RISC	
COMMUNICATION INTERFACES		
Plug-in Interface Cards	RS-232C (High-speed), IEEE 1284 , LAN or USB	
Command	SBPL	
Other Interfaces (standard)	External Port connector, RS-232C D-SUB9 pins (exclusively for Keypad)	
FONTS/BARCODE SYMBOLOGIES		
Standard Fonts	XU, XS, XM, XB, XL, OCR-A, OCR-B, Price, POP1, POP2, POP3	
Barcodes	Barcode	UPC-A/E, JAN/EAN, CODE 39, CODE 93, CODE 128, GS1-128 (UCC/EAN128), CODABAR (NW-7), Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, MSI, BOOKLAND, POSTNET, GS1 DataBar
	2D Barcode	QRCode (including Micro QR), PDF 417 (including Micro PDF417), MaxiCode , GS1 Data Matrix (ECC200)
Composite Symbols	GS1 DataBar Composite (CC-A/CC-B), GS1 DataBar Truncated Composite (CC-A/CC-B), GS1 DataBar Stacked Composite (CC-A/CC-B), GS1 DataBar Stacked Omni-Directional Composite (CC-A/CC-B), GS1 DataBar Limited Composite (CC-A/CC-B), GS1 DataBar Expanded Composite (CC-A/CC-B), GS1 DataBar Expanded Stacked Composite (CC-A/CC-B), UPC-E Composite (CC-A/CC-B), EAN-13 Composite (CC-A/CC-B), EAN-8 Composite (CC-A/CC-B), GS1-128 Composite (CC-A/CC-B/CC-C)	
OPERATING & ENVIRONMENTAL		
Power Supply Voltage	Input voltage : AC100V-240V +/-10% (full range) Rated voltage : AC100V-240V (full range)	
Power Consumption Max: 107VA / 104W	(Standby: 26VA / 24W)	
Dimensions	211mm (W) x 350mm (D) x 240mm (H), 8.31"(W) x 13.79" (D) x 9.46" (H)	
Weight	Approx. 8kg	
Temperature / Humidity	Usage Environment: 5 ~ 400C / 30 ~ 80% (No condensation) · Storage Environment: -5 ~ 600C / 30 ~ 90% (No condensation) Noise Regulations : FCC15B Class B, CE (EN55022), EN55024 , CCC, MIC · Safety Standards : UL60950-1 (2001), IEC/ EN60950-1, CCC	
OTHER STANDARDS : ROHS COMPLIANT		
Options Cutter, Stacker, External Rewinder, Dispenser, Keypad, Calendar IC		

Recommended applications:



INDUSTRY VERTICALS

- Retail
- Hospitality & Entertainment
- Transportation



APPLICATIONS

- Label & Tag Price Marking and Markdown
- Baggage Tagging
- Ticketing
- Apparel Tagging



Keypad

- Graphical LCD display, alphanumeric and function keys.
- SD card-supported.
- User conveniently keys in variable data and sends it to printer.
- Enables stand-alone printing.



Dispenser

- Simplifies separation of labels from a backing paper for immediate label application.



Stacker

- Enables neat stacking of printed tags after printing and cutting.



Rewinder

- Rewind capacity accommodates label rolls OD of up to about 70mm or 2.758"
- Ideal for batch printing applications.



Cutter

- Precisely cuts individual labels and tags.
- Allows continuous printing and cutting of labels and tags.